

DC AXIAL FAN 25x25x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 7 g Packing: 400PCS/CTN



DC Axial Fans

Model Number		Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD2510B05W3-61	★▲	5	4.0~5.75	1.40	2.50	18.70	7,000	80	0.40	B,S	①
FD2510B05W5-61	★▲	5	4.0~5.75	2.30	4.70	22.70	10,000	120	0.60	B,S	②
FD2510B05W7-61	★▲	5	4.0~5.75	3.00	8.20	29.60	13,000	160	0.80	B,S	③
FD2510B12W3-61	★▲	12	6.0~13.8	1.40	2.50	18.70	7,000	60	0.72	B,S	①
FD2510B12W5-61	★▲	12	6.0~13.8	2.30	4.70	22.70	10,000	80	0.96	B,S	②
FD2510B12W7-61	★▲	12	6.0~13.8	3.00	8.20	29.60	13,000	100	1.20	B,S	③

For "Sleeve" bearing version, change the "B" in the model number to "S"
 If model depicts "★", auto restart protection function built in.
 If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

