

# DC AXIAL FAN 30x30x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0  
 Insulation Resistance: 10M $\Omega$ , 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame  
 Operation Temperature: -10 $^{\circ}$ C~70 $^{\circ}$ C(Humidity 35%-85%RH)  
 Storage Temperature: -40 $^{\circ}$ C~85 $^{\circ}$ C(Humidity 35%-85%RH)  
 Lead Wire: UL Type #28 AWG  
 Weight: 8.5 g      Packing: 1200PCS/CTN



DC Axial Fans

Model Number		Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD3010B05W3-61	★▲	5	4.0~5.75	3.20	2.80	22.70	7,000	120	0.60	B,S	①
FD3010B05W5-61	★▲	5	4.0~5.75	4.40	4.40	26.60	9,000	140	0.70	B,S	②
FD3010B05W7-61	★▲	5	4.0~5.75	5.30	6.00	31.50	11,000	200	1.00	B,S	③
FD3010B12W3-61	★▲	12	6.0~13.8	3.20	2.80	22.70	7,000	60	0.72	B,S	①
FD3010B12W5-61	★▲	12	6.0~13.8	4.40	4.40	26.60	9,000	90	1.08	B,S	②
FD3010B12W7-61	★▲	12	6.0~13.8	5.30	6.00	31.50	11,000	100	1.20	B,S	③

For "Sleeve" bearing version, change the "B" in the model number to "S"  
 If model depicts "★", auto restart protection function built in.  
 If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

