

DC BLOWER 53x50x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #30 AWG
 Weight: 21 g Packing: 300PCS/CTN



DC Blowers

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD5010B12W3-61	★▲ 12	8.00~13.80	2.80	8.00	25.60	4,000	100	1.20	B	①
FBD5010B12W5-61	★▲ 12	6.00~13.80	3.70	14.10	31.50	5,000	170	2.04	B	②
FBD5010B12W7-61	★▲ 12	6.00~13.80	4.50	22.60	37.40	6,000	250	3.00	B	③

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

