

DC BLOWER 57x57x12mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 20 g Packing: 300PCS/CTN



Model Number	Voltage (VDC)	Op. Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD5712B05W3-81 ★	5	4.5~5.5	1.90	3.20	10.80	2,500	60	0.30	B	①
FBD5712B05W5-81 ★	5	4.0~5.5	2.70	6.50	20.70	3,500	100	0.50	B	②
FBD5712B05W7-81 ★	5	4.0~5.5	3.50	12.20	28.60	4,500	240	1.20	B	③
FBD5712B12W3-81 ★	12	10.8~13.8	1.90	3.20	10.80	2,500	40	0.48	B	①
FBD5712B12W5-81 ★	12	9.0~13.8	2.70	6.50	20.70	3,500	70	0.84	B	②
FBD5712B12W7-81 ★	12	6.0~13.8	3.50	12.20	28.60	4,500	110	1.32	B	③
FBD5712B12W9-81 ★	12	6.0~13.8	4.20	17.80	36.40	5,500	170	2.04	B	④

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

