

DC BLOWER 75x75x30mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 61 g Packing: 100PCS/CTN



DC Blowers

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD7530B12W3-81 ★	12	6.0~13.8	7.00	3.60	27.10	2,000	110	1.32	B	①
FBD7530B12W5-81 ★	12	6.0~13.8	8.70	5.60	32.60	2,500	150	1.80	B	②
FBD7530B12W7-81 ★	12	6.0~13.8	10.00	10.30	38.90	3,000	230	2.76	B	③
FBD7530B12W9-81 ★	12	6.0~13.8	12.40	12.50	43.30	3,500	280	3.36	B	④
FBD7530B12W11-81 ★	12	6.0~13.8	14.40	18.10	45.80	4,000	510	6.12	B	⑤
FBD7530B24W9-81 ★	24	12.0~27.6	12.40	12.50	43.30	3,500	230	5.52	B	⑥

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

