

# AC AXIAL FAN 80x80x25mm



**Housing:** Die-Cast Aluminum, Painted Black  
**Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 100M $\Omega$ , 500VDC/min between bare wire and frame  
**Dielectric Strength:** 1500VAC for one minute  
**Operation Temperature:** -20°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~85°C(Humidity 35%-85%RH)  
**Motor Protection:** Impedance Protected  
**Weight:** 223 g      **Packing:** 100PCS/CTN



Model Number	Voltage (VAC)	Frequency (Hz)	Air Flow (CFM)	Stat.Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA8025B11T7-51	115	50/60	18.0/22.0	2.6/3.5	25.0/32.0	2,400/2,900	70/60	6/5	B,S	①/②
FA8025B22T7-51	230	50/60	18.0/22.0	2.6/3.5	25.0/32.0	2,400/3,000	50/40	9/7	B,S	①/②

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

