

AC AXIAL FAN 92x92x25mm



Housing: Die-Cast Aluminum, Painted Black
Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minute
Operation Temperature: -20°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~85°C(Humidity 35%-85%RH)
Motor Protection: Impedance Protected
Weight: 300 g **Packing:** 50PCS/CTN

Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA9225B11T7-51	115	50/60	30.0/36.0	4.6/6.5	40.0/45.0	2,700/3,200	140/110	11/9	B,S	①/②
FA9225B22T7-51	230	50/60	30.0/36.0	4.6/6.5	40.0/45.0	2,600/3,100	70/60	12/10	B,S	①/②

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice



AC Axial Fans

